



Regular inspection of 46526 bearing

Regular maintenance of the equipment, the bearing running inspection and peripheral parts replacement was dismantled for inspection, thus judge whether the use or the use of the good or bad again. To bearing and appearance of careful investigation and records were broken down, in order to 46526 bearing understand and investigate the lubricant remaining quantity, sampling, to properly clean the bearings.

Then check the raceway surface, rolling surface and surface condition and cage wear, no damage and abnormal situation.

Judgment bearing will use again, to bearing damage degree, the machine performance, importance, operating conditions, such as checking cycle later decided. Check the results, if it is found that 46526 bearing the bearing damage and abnormal situation, wound section to find out the reason and make countermeasures. In addition, the inspection results, if there are some defects in it, the bearing can not be used, the need to replace new bearing.

A. inner and outer ring, rolling body cage in which any cracks and debris.

B. outer ring, rolling body in which any split.

C. raceway surface, block, rolling card significantly hurt.

D. cage wear or rivets loose badly.

E. raceway surface, rolling rust and bruises.

F. surface of rolling, rolling there is significant indentation and trace.

A creep of G. inner diameter of surface or outer diameter of.

H. overheating color ill.

I. grease sealed bearings seals and shields to serious damage.

(1), running inspection and fault treatment

